

by Schneider Electric

Industrial PC PS5000 SERIES

Powerful Solution





IPC Top Class Performance

Slim

Drastically slimmer profile with less wasted space. An ultra-thin design only 40% as deep as conventional products.

66% Thinner

PS-4800


High Performance

The latest technology gives this IPC excellent performance: Upgraded 280% compared to PS4000.



Smart

Multi-touch display enables operation similar to a tablet or smartphone.





PS-5811W

www.proface.com/PS50007

PS5000 Series

Full lineup to meet all your specific needs. Find your ideal combination and model on the Web. >>> http://www.proface.com/ps5000bto/



Panel Type	CPU/ Memory	Rated Voltage/ Slot	OS	Storage Media	Projected Capacitive				Resistive Film
					22″w	19″w	15″w	10″w	15″
Modular Type Replace only the Display unit for easy maintenance.	Core i7 model/ 8GB or 16GB	24VDC/ 100-240VAC 0/2 slots	Windows7 Ultimate (64bit) MUI or Windows Embedded 8.1 Industry (64bit) MUI	HDD Unit (500GB,1TB) SSD (80GB,160GB, 240GB CFast Card (16GB) *WES7 only	V	~	V		V
	Celeron model/ 4GB or 8GB				~	~	V		V
Slim Type Integrated type saves space.	Core i3 model/ 8GB	24VDC/ 100-240VAC	or Windows Embedded Standard 7 Premium (64bit) MUI			Enclosed model available.	V		
	Atom model/ 4GB	0 slot					V	~	
Box Type	CPU/ Memory	Rated Voltage/ Slot	OS		Storage Media		a	Expansion Slot	
вохтуре							a	0slot	2slot
Book mount style.	Core i7 model/ 8GB or 16GB	24VDC/ 100-240VAC	Wind Ultimate(6 o Windows En	r MUI	HDD Unit (500GB,1TB) SSD (80GB,160GB,240GB) CFast Card (16GB) *WES7 only			\checkmark	V
	Celeron model/ 4GB or 8GB	0/2 slots	Industry(6 o Windows E Standard 7 Pren	r Embedded				V	V

A Variety of Interfaces

Fan-less Design

Choose interface options for more functions such as Serial, Gigabit Ethernet, DIO and more.



No need for regular maintenance, and peace-of-mind

dispite of dust and noise at the manufacturing site.

Remote Solutions

Debugging can be done on a tablet.



Mirroring (RAID)

Replace HDD with equipment powered on. No need to stop production lines for maintenance.



Global Support

Worry-free global expansion. Repair and technical support services are available worldwide.



Flexible installation

Product can be installed with VESA mounting arm, and an enclosed model with IP66 is also available.



A WARNING

HAZARD OF OPERATOR INJURY, OR UNINTENDED EQUIPMENT DAMAGE Before operating any of these products, be sure to read all related manuals thoroughly. Failure to follow these instructions can result in death, serious injury or equipment damage.

Failure to follow these instructions can result in death, serious injury or equipment dama

For printing purposes, the colors in this catalog may differ from those of the actual unit.
Actual user screens may differ from the screens shown here.
All product names used in this catalog are the registered trademarks or trade

